


AL-AXL DAIRY



- USDA Dairy Accepted
- Versions conforming to EC 1935/2004 available
- Easy removal of rotor for fast and efficient cleaning
- Smooth product contact surfaces in food grade material
- Rotor pockets radiused and polished to Ra=0,8 µm (150 grit)
- Rotor vanes chamfered on all edges
- Flame proof and explosion shock resistant versions available
- Flameproof versions suitable for St2 products available
- Versions conforming to ATEX 94/9/EC available
- CIP-suitable versions conforming to EHEDG Type EL Class I available

AL-AXL Dairy rotary valves

The AL-AXL Dairy rotary valves have been designed for use in the food, pet food, chemical and pharmaceutical industries where very high standards apply. The Dairy valves have an official USDA certificate of acceptance for use in dairy plants and are optionally available conforming to the EC 1935/2004 directive.

The construction of the valve is designed to avoid bacteriological contamination. All product contact surfaces are in food grade material and smoothly polished.

The AL-AXL Dairy valves are optionally available in MZC execution with supporting bars for easy removal of the end cover and rotor without damaging the housing. The MZC valves are easy detachable in a few minutes.

The AL Dairy valves are available in 6 sizes, covering a capacity range from approximately 2,5 to 58 litre per revolution at 100% filling. The AXL valves are available in 4 sizes from 200-350, capacity range of the rotor from 5,5-34 litre per revolution at 100% filling. The AXL size corresponds with the dimension of the inlet flange.

Size Type AL	150	175	200	250	300	350
Size Type AXL		200	250	300	350	
Ltr/rev*	2,5	5,5	10,5	19	34	58

* at 100% filling

Product information

The body and end covers are made from AISI 316 stainless steel (DIN 1.4408). The rotor is made from AISI 316L stainless steel (DIN 1.4404). For special applications internal and external mirror polishing of the valve is possible.

The shaft sealing is by means of gland packing or air purge.

The standard models are suitable for temperatures up to 80 °C and a pressure up to 2 bar g. Flame proof and explosion shock resistant versions up to 10 bar g are also available.